MEDOUSÊ DATASHEET



Type

wall lamp

Materials and colours

transparent or green glass hemisphere with irregular surface, brass rods

Light source 230V: LED module 1x15W dimmable / rated output 15W / energy class F / lumen 1500 / K 3500* / CRI >80 / protection grade IP64

light source EPREL pending

(@110V: LED board 1x14W / rated output 14W / energy class A+ / lumen 1540 / K 3200 / CRI 80)

*The LED modules provided for Medousê F and W have a starting temperature of 2.700K, as indicated in the manufacturer's datasheets. For their outdoor use, a protective resin is applied, which increases the temperature by 800K (CCT correlated color temperature), reaching approximately 3.500K. Currently, it is not possible to provide a color temperature different from this.

Power supply

110V or 240V

Dimensions



hemisphere Ø 30 cm ca. total H rods included 44 cm

Order code

MD3P green/brass details

MD3PTR transparent/brass details

CATELLANI & SMITH SRL
VIA CIMITERO 1/A, 24020 VILLA DI SERIO, BG
CAP. SOC. € 500.000 I.V. CF, P.IVA E REG. IMPR. BG IT02656220163, ISCRIZ.
REGISTRO PILE/ACCUMULATORI N. IT25020P00010228, RIPRODUZIONE RISERVATA
© CATELLANI & SMITH

