



Type	pendant lamp
Materials and colours	transparent, green, amber glass; steel supporting cable with transparent safety sphere; grey/transparent power supply cable
Light source	<p>LED bulb G4 12V DC 1x max 1W / rated output 0,8W / energy class G / lumen 69 / K 2700 / CRI 80 / protection grade IP65</p> <p>EPREL registered light source, click here NOTE: IP specifics - lamp holder IP65 (not protected against immersion); wires IP68.</p>
Power supply	12V DC transformer not included
Dimensions	 <p>glass H 10x7 cm ca. cable length 300 cm to be cut to size</p>

Order code

MRS transparent
MRSA amber
MRSGR green

Accessories for gel box system

ED6 driver 10W 12V DC 220-240V IP67 not dimmable (max 9 lamps)
MB1 mini gel box IP68 (max 2 connections, connectors included)
MB2 mini gel box IP68 (max 6 connections, connectors included)
KP1 extension kit 5 mt con mini gel box IP68 (max 1 lamp)

Accessories for quick connectors system

ED6CR driver 10W 12V DC 220-240V IP67 not dimmable with quick connectors (max 9 lamps)
CRM multiple quick connector IP68 - 1 IN & 5 OUT (max 5 connections)
CRS single quick connector IN IP68
KP2 extension kit 5 mt with quick connectors IP68 (max 1 lamp)

CATELLANI & SMITH SRL
VIA CIMITERO 1/A, 24020 VILLA DI SERIO, BG
CAP. SOC. € 500.000 I.V. CF, P.IVA E REG. IMPR. BG IT02656220163,
RIPRODUZIONE RISERVATA © CATELLANI & SMITH

